



# PV

## Conductive polymer solid aluminum electrolytic capacitor (standard product)- SMD type

### Features

- ◆ Use for surface mounted type.
- ◆ The product can support lead free-reflow .
- ◆ RoHS Adapted to the RoHS directive.




### Specifications

Items	Characteristics				
Operating Temperature Range	-55~ +105				
Rated Voltage Range	2.5~ 25V				
Nominal Capacitance Range	22~ 2700μF				
Nominal Capacitance Tolerance	± 20% 20 120Hz				
Leakage Current	Reference parameter table 2 at 20 , after 2 minutes				
tg Dissipation Factor (Max)	20 , 120Hz	tg	5	6.3(L > 7)	6.3 (L > 7)
			0.10	0.10	0.08
ESR	Reference parameter table (m at 100k~ 300kHz 20 max)				
Characteristics of impedance ratio at high temp. and low temp.	100KHZ 20 Based the value at 100KHZ. + 20				
		-55	Z/Z20	0.75 to 1.25	
		+105	Z/Z20	0.75 to 1.25	
Load Life	+105 2000 20 After 2000 hours' application of rated voltage at 105 , and then being stabilized at +20 , the capacitors shall meet the following requirement				
	Capacitance Change	± 20% Within ± 20% of the initial value (16V: within ± 25% of the initial value)			
	Dissipation Factor	150% Not more than 150% of the initial specified value			
	Equivalent Series Resistance	150% Not more than 150% of the initial specified value			
	Leakage Current	Not more than the initial specified value			
Damp heat(Steady state)	60 , 90~ 95% RH, 1000 60 , 90~ 95% RH, 1000 hours, No-applied voltage.				
	Capacitance Change	± 20% Within ± 20% of the initial value (16V: within ± 25% of the initial value)			
	Dissipation Factor	150% Not more than 150% of the initial specified value			
	Equivalent Series Resistance	150% Not more than 150% of the initial specified value			
	Leakage Current	Not more than the initial specified value			
Resistance to Soldering Heat	VPS (260 X 10s)				
	Capacitance Change	± 10% Within ± 10% of the initial value (16V : within ± 15% of the initial value)			
	Dissipation Factor	Not more than the initial specified value			
	Equivalent Series Resistance	Not more than the initial specified value			
	Leakage Current	Not more than the initial specified value			

: 125 120  
When in doubt, apply the following voltage treatment and measure.  
Voltage processing: under the condition of 125 ambient temperature, continuous load voltage of 120 minutes. Load voltage is rated voltage.

### Dimensions



## Size List

	5x 5.8	6.3x 5.8	6.3x 7.7	8x 10.5	8x 12.5	10x 10.5	10x 12.5
A	2.1	2.4	2.4	2.9	2.9	3.2	3.2
	5.3	6.6	6.6	8.3	8.3	10.3	10.3
C	5.3	6.6	6.6	8.3	8.3	10.3	10.3
E	1.3	2.2	2.2	3.1	3.1	4.5	4.5
	5.8	5.8	7.7	10.5	12.5	10.5	12.5
H	0.5~0.8			0.8~1.1			

## Nominal Capacitance, Rated Voltage, Rated Ripple Current and Case Size Table

Rated Volt. (V)	Capacitance ( $\mu$ F)	Size D x L(mm)	Tan 120HZ,20	LC $\mu$ A	ESR (mΩ at 100kHz~300kHz 20°C max)	Rated R. C. (mA/rms at 100kHz 105°C)
2.5	180	5x 5.8	0.1	300	30	2100
		6.3x 5.8	0.1	300	25	2500
	270	6.3x 5.8	0.1	300	25	2500
	330	6.3x 5.8	0.1	300	25	2700
	390	6.3x 5.8	0.1	300	25	2700
	470	6.3x 7.7	0.1	300		3700
	560	6.3x 7.7	0.1	300		3700
	680	8x 10.5	0.08	340	15	4100
	820	8x 10.5	0.08	410	15	4100
	1000	8x 10.5	0.08	500	15	4100
	1200	8x 12.5	0.08		12	4300
	1500	8x 12.5	0.08	750	12	4300
		10x 10.5	0.08	1100	12	4700
	2700	10x 12.5	0.08	1350	12	4700
4	100	5x 5.8	0.1	300	30	1800
	150	5x 5.8	0.1	300	30	1800
		6.3x 5.8	0.1	300	25	2500
	270	6.3x 5.8	0.1	300	25	2500
	330	6.3x 5.8	0.1	300	25	
	390	6.3x 5.8	0.1	312	25	
	470	6.3x 7.7	0.1	376		3100
	560	6.3x 7.7	0.1	448		3100
	680	8x 10.5	0.08	544	15	4100
	820	8x 10.5	0.08	656	15	4100
	1000	8x 10.5	0.08	800	15	4100
	1200	8x 12.5	0.08	960	12	4700
	1500	8x 12.5	0.08	1200	12	4700
		10x 10.5	0.08	1760	12	5400
	2700	10x 12.5	0.08	2160	12	5400
6.3	100	5x 5.8	0.1	300	30	1500
	100	6.3x 5.8	0.1	300	25	2400
	120	5x 5.8	0.1	300	30	1500
	120	6.3x 7.7	0.1	300		
	150	6.3x 5.8	0.1	300	25	2400
		6.3x 5.8	0.1	300	25	2400
		6.3x 7.7	0.1	300		
	330	6.3x 7.7	0.1	415		
	470	6.3x 7.7	0.1	592		
	680	8x 10.5	0.08	856	15	4100
	820	8x 10.5	0.08	1033	15	4100
	1000	8x 10.5	0.08	1260	15	4100
	1200	8x 12.5	0.08	1512	12	4700



Rated Volt. (V)	Capacitance ( $\mu$ F)	Size D×L(mm)	Tan 120Hz,20	LC $\mu$ A	ESR (m /at 100k~300kHz 20 max)	Rated R. C. (mA/rms at 100kHz 105 )
6.3	1500	8×12.5	0.08	1890	12	4700
		10×10.5	0.08	2772	12	5400
	2700	10×12.5	0.08	3400	12	5400
10	47	5×5.8	0.1	300	40	1300
	56	5×5.8	0.1	300	40	1300
	56	6.3×5.8	0.1	300	30	2100
	68	6.3×5.8	0.1	300	30	2100
	120	6.3×5.8	0.1	300	30	2100
	150	6.3×7.7	0.1	300	25	2500
		6.3×7.7	0.1	440	25	2500
	270	6.3×7.7	0.1	540	25	2500
	470	8×10.5	0.08	940		3700
	560	8×10.5	0.08	1120		3700
	680	8×10.5	0.08	1360		3700
	820	8×12.5	0.08	1640	15	4300
	1000	8×12.5	0.08		15	4300
	1200	10×10.5	0.08	2400	15	5200
	1500	10×12.5	0.08	3000	15	5200
16		5×5.8	0.1	300	45	1200
	33	5×5.8	0.1	300	45	1200
	39	5×5.8	0.1	300	45	1200
	39	6.3×5.8	0.1	300	40	1600
	47	6.3×5.8	0.1	300	40	1600
	68	6.3×5.8	0.1	300	40	1600
	82	6.3×5.8	0.1	300	40	1600
	100	6.3×5.8	0.1	320	40	1600
	100	6.3×7.7	0.1	320	35	2300
	150	6.3×7.7	0.1	480	35	2300
	330	8×10.5	0.08	1056	30	3700
	470	8×10.5	0.08	1504	30	3700
	560	8×10.5	0.08	1792	30	3700
	680	8×12.5	0.08	2176	25	4100
	820	10×10.5	0.08	2624	25	5100
	1000	10×12.5	0.08	3200		5100
25		6.3×5.8	0.1	300	50	1600
	47	6.3×5.8	0.1	300	50	1600
	56	6.3×5.8	0.1	300	50	1600
	100	6.3×7.7	0.1	400	45	1800
	120	6.3×7.7	0.1	480	45	1800
		8×10.5	0.08	880	30	3100
	270	8×10.5	0.08	1080	30	3100
	330	8×10.5	0.08	1320	30	3100
	390	8×10.5	0.08	1560	30	3100
	470	8×12.5	0.08	1880	25	3700
	680	10×10.5	0.08	2720	25	4300
	820	10×12.5	0.08	3280	25	4300
	47	6.3×5.8	0.1	300		1200
	56	6.3×5.8	0.1	300		1200